NOTES: 1. (M): FAM MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BPT DENOTES FEMALE PIPE THREAD BPW DENOTES HEAD BPW DENOTES BEVELED FOR WELDING GVD DENOTES GROWLED FLG DENOTES PLANGE PE DENOTES PLANGE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 KPa], 50 psi MAX [344 KPa] 6. "-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FARRICATION OF CONNECTINO PIPING 7. 34" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm]  FACE A  FACE A	MODEL # ATC-XE553E SCALE NTS	FVAP(()			
1. (M)- FAM MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BFV DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FEALS PIPE THREAD BFV DENOTES PHAINE PE DENOTES PH		LVAP CO,	TIVC.	SERIAL #	DATE 8/26/2025
1'-3 1/4" [ 387 ]  - 4'-9" * - 2'-6 3/8" * [ 772] *  9'-8 5/8" [ 2964]	1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN			ACCESS DOOR	FACE D
3'-3 1/4" (2) 4' [100] PE REFRIG OUT (4543)  2" [50] MPT (154] * [154] * [1580]  2-1 1/4" (108] (133) (1433)  3 5/8" (1433) (143	3'-3 1/4" * (2) 4" [100] PE REFRIG IN  2" [50] MPT REFRIGOUT  2" [50] MPT REFRIGOUT  2" [643]  3 5/8"  3 5/8"  4 1/4"  [ 108]  - 4 1/4"  [ 108]  - 5'-11 3/4"  - [ 2991]	2'-6 3/8" *  9'-8 5/8"  [ 2964]  14'-10 7/8"  [ 4543]		18'-0" [ 5486]	