| UNIT CLOSED CIRCUIT COOL | | DOLER | EVAPCO, INC. | | evanço | DWG. # WB3122006-DR | C-ST REV |
|---|--|--|-----------------------------------|---------------------|--------------|---------------------|----------------------------|
| MODEL # | ATWB 12-3N20 | SCALE NTS | EVAPC | O, INC | | SERIAL # | DATE _{12/13/2025} |
| 2. HÉAVIE 3. MPT DI FPT DE BFW D GVD D FLG DE PE DEI 4. +UNIT 5. MAKE- 20 psi N 6. *-APPE FOR PI PIPING 7. 3/4" [18 RECON | IN MOTOR LOCATION EST SECTION IS UPPER SI ENOTES MALE PIPE THRE ENOTES FEMALE PIPE THE ENOTES BEVELED FOR W ENOTES FLANGE NOTES PLAIN END WEIGHT DOES NOT INCLUSORIES (SEE ACCESSOR UP WATER PRESSURE WIN [137 kPa], 50 psi MAX [3 EXCIMATE DIMENSIONS DO RE-FABRICATION OF CONI MMENDED STEEL SUPPOR SIONS LISTED AS FOLLOV ENGLISH FT-IN | AD READ FELDING JDE Y DRAWINGS) 344 kPa] O NOT USE NECTING ES. REFER TO RT DRAWING. | | FACE B PLAN VIEW | | FACE C ACCESS DOOR | FACE D |
| | METRIC [mm] | | | | | FACE A | |
| | | | 7" [178] | | | | |
| | ,- <u></u> | | | 1'-3 [3 | 1/4" 87] | | |
| | <u> </u> | | | | | | Т |
| | | 5'-9 1/4" * - - - - - - - - - - | 3'-3/8" * | (2) 1/2 | 2" [15] \ | (**) | |
| | 1'-10 1/4" * (2) 4" [1 | O O FLUID IN | 8'-3 5/8" [2532] | FPT \ | VENT | | |
| | [565] (2) 4" [100] | BFW FLUID OU | T 14'-5 [44 | 7/8" .6] | | A . | |
| | 2" [50] MPT — MAKE-UP — 2'-1 1/4" — [643] | | 6" * 6'-2 1/4" [1884] 1'-5" [433] | | | | |
| | 3 5/8" DRĀI [92] - 51 [13] - 41/ [10] | /4" 33] '4" 8] | IPT V | | | | |
| | [2 | 7'-2" 184] | | 2'-1/2" [622] | | 20'-0" [6096] | |