| UNIT CLOSED CIRCUIT COOLER | | | EVAPCO, INC. EVEPCO SERIAL # WV050912-DRC-ST | | | | REV. |
|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------------------------------------|---------------------------|-----------------------------------------|----------------------------|-----------------------|
| MODEL # | eco-LRWB 5-6K9 | SCALE NTS | EVAPCO |), INC. | S | ERIAL # | DATE 8/19/2025 |
| 2. MPT D FPT D BFW I GVD D FLG D PE DE 3. +UNIT ACCE: 4. 3/4" [1 RECO 5. DIMEN 6. * - APF USE F 7. MAKE | AN MOTOR LOCATION DENOTES MALE PIPE THREA ENOTES FEMALE PIPE THREA ENOTES BEVELED FOR WID DENOTES GROOVED ENOTES FLANGE NOTES PLAIN END WEIGHT DOES NOT INCLUI ESSORIES (SEE ACCESSORY OF MIDDEN STEEL SUPPOR' ISIONS LISTED AS FOLLOW PROXIMATE DIMENSIONS D OR PRE-FABRICATION OF COUP WATER PRESSURE [137 kPa] MIN, 50 psi [344 kP | EEAD ELDING DE (DRAWINGS) ES. REFER TO T DRAWING ('S: ENGLISH FT I | DI AN VIEW | | FACE C | | FACE D |
| | - - 2'-6 3/8" * - | | | 2 | 15'-2 1/4" [4629] FACE A | | _ |
| | 0] BFW UID IN | | | 1/2" [15] FPT VENT | 5 | 6'-3" [1905] | |
| | O] BFW O | [] | 5'-6" [1678] 8'-6 1/4" [2597] | | | | 6'-7 3/4" [2026] |
| 3 1/4' [83] | TYP | | 5 1/4" * | | CCESS | | 1'-8 1/8" |
| OVER | o] MPT | | 2 5/8" 8 3/4" [67] 222] 4 7/8" [124] | | '-5 3/8" 2575] | 1" [25] MPT MAKE-UP | ACCESS DOOR |
| | DRAIN 5'-5/8 [1540 | <u>B</u> | 1'-1 5/8" — — | | 15'-2 1/4" [4629] FACE A | | _ |
| SHIPPING WEIGHT | 8800 lbs+ [399 | 5] kg+ | OPERATING 12920 lbs+ [5865] kg WEIGHT | + HEAVIEST SECTION WEIGHT | 8800 lbs+ [3995] kg+ | NO. OF SHIPPING SECTIONS 1 | DRAWN BY: TLS |