

NOTES:

1. (M)- FAN MOTOR LOCATION
2. HEAVIEST SECTION IS LOWER SECTION
3. MPT DENOTES MALE PIPE THREAD
FPT DENOTES FEMALE PIPE THREAD
BFW DENOTES BEVELED FOR WELDING
GVD DENOTES GROOVED FOR VICTAULIC
4. +UNIT WEIGHT DOES NOT INCLUDE
ACCESSORIES (SEE ACCESSORY DRAWINGS)
5. MAKE-UP WATER PRESSURE
20 psi MIN [137 kPa], 50 psi MAX [344 kPa]
6. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO
RECOMMENDED STEEL SUPPORT DRAWING
7. DIMENSIONS LISTED AS FOLLOWS: ENGLISH IN
[METRIC] [mm]

**FACE 1
PLAN VIEW**

FACE 1 PLAN VIEW diagram showing a rectangular unit with various dimensions and labels. The unit is 7'-10" [2388] wide and 13'-6 1/4" [4120] high. It features an access door, overflow, make-up, and drain connections, and an 8 [200] BFW/GVD outlet. Dimensions are listed in inches and millimeters.

FACE 1

**FACE 1
PLAN VIEW**

FACE 1 PLAN VIEW diagram showing a rectangular unit with various dimensions and labels. The unit is 7'-10" [2388] wide and 13'-6 1/4" [4120] high. It features an access door, overflow, make-up, and drain connections, and an 8 [200] BFW/GVD outlet. Dimensions are listed in inches and millimeters.

FACE 2

FACE 2 PLAN VIEW diagram showing a rectangular unit with various dimensions and labels. The unit is 18'-0" [5486] wide and 13'-6 1/4" [4120] high. It features an 8 [200] BFW/GVD inlet and an 8 [200] BFW/GVD outlet. Dimensions are listed in inches and millimeters.

FACE 2

SHIPPING WEIGHT	8440 lbs+ [3828] kg+	OPERATING WEIGHT	13790 lbs+ [6255] kg+	HEAVIEST SECTION WEIGHT	5440 lbs+ [2468] kg+	NO. OF SHIPPING SECTIONS	2
-----------------	----------------------	------------------	-----------------------	-------------------------	----------------------	--------------------------	---