| COOLING TOWER   |  |   | EV                        | ADCO T              |                            | apco                                  | wg. # AX122217-DRA  | AX122217-DRA-ST REV.                            |  |
|---|--|---|---------------------------|---------------------|----------------------------|---------------------------------------|---|---|--|
| MODEL #   | AXS 12-19L22   | SCALE                                   | ] EV/                     | APCO, I             | NC.                        | S                                     | ERIAL #   | DATE<br>9/5/2025                                |  |
| 2. HEAVIEST 3. MPT DENO FPT DENO BFW DENC GVD DENC 4. +UNIT WEI ACCESSOF 5. MAKE-UP V 20 psi MIN 6. 3/4" DIA. M RECOMME | OTOR LOCATION SECTION IS UPPER SECTIONS IS UPPER SECTION IS UPPER SECTIONS IN UPPER SECTIONS IN UPPER SECTIONS IN UPPER SEVELED FOR WELLISTES GROOVED GHT DOES NOT INCLUDE RIES (SEE ACCESSORY DOWNTER PRESSURE [137 kPa], 50 psi MAX [344 OUNTING HOLES. REFER NDED STEEL SUPPORT IN UPPER SUPPER SUPPE | AD DING  E RAWINGS)  kPa] t TO DRAWING. |                           | FACE B<br>PLAN VIEW | 5'-11"<br>1804 ]<br>V      | FACE C ACCESS DOOR                    |   | FACE D  (2) 8" [200] ASME 150 FLG PATTERN INLET |  |
|   |  |   | 7"<br>[ 178 ]             |                     |                            | FACE A                                |   |   |  |
|   |  |   | 9'-4 3/8" [ 2855 ]        | 4"                  |                            |                                       | ·••   | ∕− 4" [100] FPT<br>OVERFLOW                     |  |
|   |  |   | 9'-11 5/8"<br>[ 3038 ]    | <b>3</b> ]          | <u> </u>                   | ACCESS DOOR                           |   | 3" [80] MPT<br>MAKE-UP<br>4" [100] FPT<br>DRAIN |  |
|   |  | 11'-10"<br>3607 ]<br><b>FACE</b>        | 3/8"<br>[ 10 ]            | 3 7/8"              |                            | [300] BFW/GVD OUTLET  22'-9" [ 6934 ] | 9'-3"<br>[ 2819 ]<br>10'-1"<br>[ 3073 ]<br>— 11'-4 1/2"<br>[ 3467 ] |   |  |
| SHIPPING<br>WEIGHT  | 16600 lbs+ [7530] l  | kg+                                     | OPERATING WEIGHT 37540 lk | os+ [17030] kg+     | HEAVIEST SECTION<br>WEIGHT | 9420 lbs+ [4275] kg+                  | NO. OF SHIPPING SECTIONS  | 2 DRAWN BY: JLM                                 |  |