COOLING TOWER		R	EVADOO TRIC (EVCIDED)® AX142413	3-DRA-ST	REV.
MODEL #	AXS 14-16K24	SCALE	EVAPCO, INC. EVAPCO SERIAL #		DATE 9/5/2025
2. HEAVIE: 3. MPT DE FPT DEI BFW DE GVD DE 4. +UNIT W ACCESS 5. MAKE-U 20 psi M 6. 3/4" DIA RECOM	I MOTOR LOCATION ST SECTION IS UPPER SEC NOTES MALE PIPE THREAD NOTES FEMALE PIPE THREAD NOTES BEVELED FOR WEI NOTES GROOVED VEIGHT DOES NOT INCLUD SORIES (SEE ACCESSORY IN P WATER PRESSURE IN [137 kPa], 50 psi MAX [344] MOUNTING HOLES. REFER MENDED STEEL SUPPORT HONS LISTED AS FOLLOWS	D AD LDING E DRAWINGS) 4 kPa] R TO DRAWING.		(2)	<b>FACE D</b> 10" [250] ASME BOLT PATTERN ET
			7"		
7" [ 178 ]					
			9'-4 3/8" [ 2855 ] [ 4825 ]	OV 3" MA	[100] FPT ERFLOW [80] MPT KE-UP [100] FPT AIN
			6'-5 5/8" [1970]		
		'-11 1/4" 48 ] CE B	3/8" 2'-5 3/4" 14" [350] BFW/GVD OUTLET [3124] 11'-1" [3378] 12'-4 1/2" [3772] 7544] FACE A	<b>-</b>	
SHIPPING WEIGHT	19820 lbs+ [8995] k	(g+	OPERATING WEIGHT 46470 lbs+ [21080] kg+ HEAVIEST SECTION 11720 lbs+ [5320] kg+ NO. OF SHIPPING SECT	IONS 2	DRAWN BY: AWT