UNIT CONDENSER			EV/AD	CO TR	ALC RY	apeo	DWG. # WV050906-DRC-ST	REV.
MODEL #	LRC-108	SCALE NTS	EVAP	CO, II	VC.	1	SERIAL #	DATE 8/17/2025
FPT DENOTES BFW DENOTE GVD DENOTE FLG DENOTES PE DENOTES 3. +UNIT WEIGH	S MALE PIPE THREAD S FEMALE PIPE THREAD S BEVELED FOR WELD S GROOVED S FLANGE	DING				FACE C		
4. 3/4" [19mm] DI RECOMMEND 5. DIMENSIONS 6. * - APPROXIM, USE FOR PRE 7. MAKE-UP WA	A. MOUNTING HOLES. F ED STEEL SUPPORT DF LISTED AS FOLLOWS: E [ATE DIMENSIONS DO N -FABRICATION OF CON	REFER TÓ RAWING ENGLISH FT II [METRIC] [mm IOT INECTING PIF	FACE B 5'-	5/8"				FACE D
					73			
-	2'-6 3/8" *						6'-3" [1905]	
4" [100] PE - REFRIG IN 4" [100] PE - REFRIG OUT		1'-7	3'-7 1/2" [1106] 195] * 6'-7 3/4" [2026]			CCESS DOOR		6'-7 3/4" [2026]
3 1/4" [83] TYP. →		Mo	3'-1/4" [919] 2 5/8"					1'-8 1/8"
3" [80] MPT — OVERFLOW		- <u>'</u>	2 5/8"	-		8'-5 3/8" [2575]	└─ 1" [25] MPT MAKE-UP	ACCESS DOOR
2" [50] MPT — DRAIN	5'-5/8" [1540] FACE B	1'-8 7/8"		1 5/8"		15'-2 1/4' [4629] <u>FACE A</u>		
SHIPPING WEIGHT	5250 lbs+ [2385] kç	g+	OPERATING 8070 lbs+ [3	8665] kg+	HEAVIEST SECTION WEIGHT	5250 lbs+ [2385] kg+	NO. OF SHIPPING SECTIONS 1	DRAWN BY: TLS