NOTES IN MAN MOTOR LOCATION IN MAN MOTOR LO	UNIT CONDENSER			EVADOO TNO EVEDEO			DWG. # WB3241206-DRD	o-ST REV
1. (M.) FAN MOTOR LOCATION 2. HAVEST SECTION IS UPPER SECTION 3. MET DINOTES MALE PIPE THERAD 3. MET DINOTES MALE PIPE THERAD 3. MET DINOTES FLANCE GVD DENOTES GROOVED 4. FLANT WEIGHT DOES NOT INCLUDE 4. FLANT WEIGHT DOES NOT INCLUDE 4. FLANT WEIGHT DOES NOT INCLUDE 3. DIPAINING 1579-1, John MIN (1740 NOT) LOS 5. MAKE-UP WATER PIPESSURE 7. 364 1 Flanm DIA MOUNTING HOLES REFER TO 7. 364 1 Flanm DIA MOUNTING HOLES REFER TO 8. RECOMMENDED STEEL SUPPORT DRAWING. 9. DRIENSING TOM OF CONNECTING PIPING 8. DRIENSING TOM OUT THE SUPPORT DRAWING. 9. DRIENSING TOM OUT THE SUPPORT DRAWING. 9. DRIENSING TOM OUT THE SUPPORT DRAWING. 1. 1789 1 Flank DIA MOUNTING HOLES REFER TO 8. PERCENDANCE OF THE SUPPORT DRAWING. 9. DRIENSING TOM OUT THE SUPPORT DRAWING. 1. 1789 1 Flank DIA MOUNTING HOLES REFER TO 8. PERCENDANCE OF THE SUPPORT DRAWING. 1. 1789 1 Flank DIA MOUNTING HOLES REFER TO 8. PERCENDANCE OF THE SUPPORT DRAWING. 1. 1789 1 Flank DIA MOUNTING HOLES REFER TO 8. PERCENDANCE OF THE SUPPORT DRAWING. 1. 1789 1 Flank DIA MOUNTING HOLES REFER TO 1. 1789 1 Flank DIA MOUNTING HOLE	MODEL #	eco-ATC-871A	SCALE NTS	EVAPCO, I	INC.		SERIAL #	DATE 7/7/202
1'-10 1/4" * (4) 4' 100) PE	1. (M)- FA 2. HEAVIE 3. MPT DI FPT DE BFW D GVD DI FLG DE PE DEN 4. +UNIT ACCES 5. MAKE-I 20 psi N 6. *-APPR FOR PF FOR PF FOR PI 7. 3/4" [19 RECON	EST SECTION IS UPPER S ENOTES MALE PIPE THRE ENOTES FEMALE PIPE THI ENOTES BEVELED FOR W ENOTES GROOVED ENOTES FLANGE NOTES PLAIN END WEIGHT DOES NOT INCLU SSORIES (SEE ACCESSOR UP WATER PRESSURE MIN [137 kPa], 50 psi MAX [ROXIMATE DIMENSIONS DI RE-FABRICATION OF CON DOMM] DIA. MOUNTING HOL MMENDED STEEL SUPPOF SIONS LISTED AS FOLLOW ENGLISH FT-IN	EAD READ VELDING JDE LY DRAWINGS) 344 kPa] O NOT USE NECTING LES. REFER TO RT DRAWING.		PLA	FACE B N VIEW	(2) ACCESS DOOR	FACE D
[130]		2'-1 1/4" [643] 3 5/8"	4" 1001 PE REFRIG OU O O O O O O O O O O O O O O O O O O	(4) 4" [100] PE (4) 4" [100] PE (4) 4" [100] PE (154] (154) (154] (154] (154) (154] (154) (154] (154) (154] (154)	8'-3 5/8" [2532] 14'-5 7/8" [4416]	· · · · · · · · · · · · · · · · · · ·		

HEAVIEST SECTION WEIGHT

14240 lbs+ [6460] kg+

SHIPPING WEIGHT OPERATING WEIGHT

47120 lbs+ [21375] kg+

33900 lbs+ [15380] kg+

DRAWN BY: SLR

NO. OF SHIPPING SECTIONS