NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS COIL SECTION 3. MET DENOTES MALE PIPE THREAD PET DENOTES FEMALE PIPE THREAD BYW DENOTES BEWLELD FOR WELDING GVO DENOTES GROVED 1. LIGHT STANCE 1. LIG	CLOSED CIRCUIT COOLER	FVΔPCΩ	INC. Evapeo	DWG. # WX409183612P-DRA-ST REV -
1. (M.) FAN MOTOR LOCATION 2. (EAVINESS SECTION 2. LEVERS SECTION	ESW4 9-36I18-LP NTS			DATE: 9/11/2025
ENGLISH FT-IN METRIC [mm] 8. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PREK-RABRICATION OF CONNECTING PIPING 9. COIL CONNECTIONS LOCATED ON FACES B AND D  **2.8"** * *2.2 3/8" (670)  **COIL CONNECTIONS**  **COIL COIN COIL COIL COIL COIL COIL COIL COIL COIL	BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. 3/4" [19MM] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING 6. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa]		FACE B PLAN VIEW  (2) 4" [100] BFW FLUID OUT  -* 3'-6" [1067]	(M) FACE D
COIL CONNECTIONS  2" [S0] MPT	ENGLISH FT-IN [METRIC] [mm]  8. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPIN  9. COIL CONNECTIONS LOCATED ON FACES B AN	IG ID D * 2'-8" [813]	* 2'-2 3/8" [670] * 2'-10 3/4" [883]	1'-0 7/8" [327]
2" [50] MPT			L (DOOR	) Series Door
2'-3" [686] 3 3/8" [86] 4 1/4" [107] 5 1/4" [132] 8'-5 1/2" [2578] 1'-6 3/8" [465] 2'-2 1/4" [667] 18'-0" [5486] FACE A	2" [50] MPT —	3" [80] MPT OVERFLOW	(2)1/2" [15] FPT VENT	19'-0 3/8" [5802
3 3/8" [86] 4 1/4" 2'-5 5/8" 2'-2 1/4" 18'-0" [5486]  5 1/4" [132] 8'-5 1/2" [2578]	2'-3" [686]	1'-6 3/8" [465]		
FACE B	4 1/4" [107] 5 1/4" [132] 8'-5 1/2" [2578]	2'-5 5/8"	[667]	486]
SHIPPING WEIGHT 23670 lbs+ [10740] kg+ OPERATING WEIGHT 33510 lbs+ [15200] kg+ HEAVIEST SECTION WEIGHT 17180 lbs+ [7795] kg+ NO. OF SHIPPING SECTIONS 2 DRAWN BY: AWT	SHIPPING 23670 lbs+ [10740] ka+ OPER	ATING 33510 lhs+ [15200] ka+	HEAVIEST SECTION 17180 lbs+ [7795] ka+	NO. OF SHIPPING SECTIONS 2 DRAWN BY: