| UNIT CLO | SED CIRCUIT COOLER | | | TNO I | | DWG.# WX409123610P-DRA-ST | REV _ |
|--|---|--------------------|---|----------------------------|-----------------------|----------------------------------|-----------------|
| MODEL# | ESW4 9-35L12-SP | NTS | EVAPCO, | INC. | | SERIAL# | DATE: 9/12/2025 |
| 2. HEAVIII 3. MPT DI FPT DE BFW D GVD D FLG DE 4. +UNIT ACCES 5. 3/4" [19 REFER SUPPO 6. MAKE- 20 psi Î 7. DIMEN ENO | IN MOTOR LOCATION EST SECTION IS COIL SECTION ENOTES MALE PIPE THREAD ENOTES FEMALE PIPE THREAD ENOTES BEVELED FOR WELDII ENOTES GROOVED ENOTES FLANGE WEIGHT DOES NOT INCLUDE SSORIES (SEE ACCESSORY DR. DIMM] DIA. MOUNTING HOLES. R TO RECOMMENDED STEEL DRT DRAWING UP WATER PRESSURE MIN [137 kPa], 50 psi MAX [344 kF SIONS LISTED AS FOLLOWS: GLISH FT-IN TRIC] [mm] | NG AWINGS) | | FACE B PLAN VIEW | FACE C | FACE D | |
| 8. * - APP | ROXIMATE DIMENSIONS DO NO RE-FABRICATION OF CONNECT | | | | FACE A | _[1'-0 7/8" [327] | |
| | (M) * 2'-8" [813] | <u>-</u> | | | | ACCESS DOOR 8'-3 1/4" [2522] | |
| | 4" [100] BFW FLUID IN 2" [50] MPT MAKE-UP | | 4" [100] BFW FLUID OUT 3" [80] MPT OVERFLOW -* 2'-10 1/2" [876] | 1/2" [15] FPT VENT | | 17'-8 7/ | B" [5409] |
| | 2" [50] MPT DRAIN 2'-3" [686] | | | | | 9'-5 5/8" [2887] | 1 |
| | 3 3/8" [86] | | L* 2'-2 3/8" [670] 1'-6 3/8" [465] 2'-5 5/8" | 2'-1"_ [635] | 11'-11 3/4" [3651] | | |
| | | 5 1/2"578] | [752] * 2'-10 3/4" [883] | | | | |
| FACE B | | | 0 22220 lbc - [40000] lcc - | HEAVIEGT SECTION | 11620 lba [5290] kg | NO. OF SHIPPING SECTIONS | DRAWN BY: |
| SHIPPING WEIGHT | 15490 lbs+ [7030] kg+ | OPERATIN WEIGHT | g 22220 lbs+ [10080] kg+ | HEAVIEST SECTION WEIGHT | 11630 lbs+ [5280] kg+ | NO. OF SHIPPING SECTIONS 2 | AWT |