| UNIT COOLING TOWER | | | EVAPCO, INC. Evapeo | | | apco | DWG. # T3BI422660-DRD-ST | | REV. |
|--|--|---|--|---|--|--|---------------------------|-------|----------------|
| MODEL # | AT 342-5O26 | SCALE NTS | | VAPCO, II | VC. | 9 | ERIAL # | | DATE 8/25/2025 |
| 2. HEAVI 3. MPT D BFW D GVD D FLG D 4. +UNIT ACCES 5. MAKE- 20 psi 6. PAN E OTHEI 7. FOR B SEE D 8. 3/4" [1 RECO 9. DIMEN | AN MOTOR LOCATION JEST SECTION IS UPPER SE DENOTES MALE PIPE THREA ENOTES FEMALE PIPE THREA ENOTES BEVELED FOR WE DENOTES GROOVED ENOTES FLANGE WEIGHT DOES NOT INCLUI SSORIES (SEE ACCESSORY -UP WATER PRESSURE MIN [137 kPa], 50 psi MAX [34 QUALIZER PIPING IS SUPPL RS, FLUME SUPPLIED BY EV SOTTOM CONNECTION SPEC JETAIL. 9mm] DIA. MOUNTING HOLE MMENDED STEEL SUPPORT JSIONS LISTED AS FOLLOW NGLISH FT-IN METRIC] [mm] | DE DE DRAWINGS) 44 kPa] LIED BY APCO. CIFICATIONS, S. REFER TO DRAWING S: 2 1/8 | INSID BO | FACE B 14'-5 1/2" 1 E BASIN TTOM 2 1/8" +1/4 | (3) 14" [350] — BFW/GVD EQUALIZER (3) 14" [350] — BFW/GVD OUTLET (3) 14" [350] — BFW/GVD INLET 2'-10 1/2" 11'-3 1/2" [3924] | (2) ACCESS DOOR (2) ACCESS DOO | CESS DOOR (2) ACCESS DOOR | ACE D | |
| | | | CAL BOTTOM CTION DETAIL | | | FACE | | | |
| | 25'-8 [78 FAC | | 12'-1/8" [3661] 22'-3 [679] 10'-3 3/8" [3134] | 2'-2" [660] | 1'-3 1/4" | 13'-5 1/2" - (3') 13'-6 1/2" - (3') | 5] | | |
| SHIPPING WEIGHT | 75420 lbs+ [3421 | 0] kg+ | OPERATING WEIGHT | 125910 lbs+ [57115] kg+ | HEAVIEST SECTION WEIGHT | 18160 lbs+ [8240] kg+ | NO. OF SHIPPING SECTIONS | 6 DI | RAWN BY: |