CONDENSER			EVAPCO, INC. EVAPCO		CEWR124012-DRA-ST	REV -
IODEL#	MRC-1985	SCALE NT	EVAPCO, IN		SERIAL #	DATE: 12/13/2025
4. 3/4" [19mm] DIA. MC RECOMMENDED STEI 5. MAKE-UP WATER PRI 50 psi [344 kPa] MAX 6. DIMENSIONS LISTED ENGLISH FT-IN [METRIC] [mm] 7. * - APPROXIMATE DI	PIPE THREAD LE PIPE THREAD LED FOR WELDING DYED SE END S NOT INCLUDE ACCESSORY DRAWINGS; DUNTING HOLES. REFER EL SUPPORT DRAWING. ESSURE 20 psi [137 kPa]	ER TO G. a] MIN,	FACE B PLAN VIEW	FACE C		FACE D
3'-0 7/8		3 5/8" * _ ,		FACE A		
OVERSIZED — ACCESS DOORS 3"[80] MPT [130] 3"[80] MPT DRAIN — 1'-8"[508] 3 7/8" [98]	(4) 4" [100] PE	REFRIG OUT	3'-11 3/4" [1213] * 7'-2 5/8" [2200] 15'-9" [4801] 9'-11" [3023] * 8'-6 3/8" [2600] 2'-3 1/4" (2) 3"[80] MPT OVERFLOW	40'-2" [12243]	(M) ⁻ (M)	2'-5 1/8" [740]
SANDENIA .	[36 FA 6	10 3/8" 8616] .CE B	OCEDATING UESAVE	FACE A	NO. OF SHIPPING SECTIONS	DRAWN BY: II C
SHIPPING 74 WEIGHT	4580 lbs+ [33830] l	kg+	OPERATING 91300 lbs+ [41415] kg+ HEAVIES W	28390 lbs+ [12880] kg+	NO. OF SHIPPING SECTIONS 3	DRAWN BY: JLG