COUNTS SOFTMENT IN THE WAY OF THE				
FACE C  1.0F (M POTOR) COURTING  2. MET PRINTED SAME PRINT THERM OF THE THE MAN AND THE MA	CONDENSER	EVADOO TNO evapoo	DWG. # CEWR123608-DRA-ST	REV -
1. (a) F AM STORE LOCATION L.  2. PET PLANTS AND RED PRINCED  3. PET PLANTS AND RED  4. PET PLANTS AND RED  5. PET PLANTS AND RED  6. PE	eco-PMRC-1511 SCALE NT	EVAPCO, INC.	SERIAL#	
3*-0 7/8"* 5'-8 5/8"   [1743]  OVERSIZED OF REFINION 2*-6 3/4" [781]    OVERSI	BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END  3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS).  4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING.  5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [344 kPa] MAX.  6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] [mm]  7. * - APPROXIMATE DIMENSIONS DO NOT	FACE B	<u>C</u>	FACE D
OVERSIZED ACCESS DOORS 3"[80] MPT [130]		FACE	<u>. A</u>	
	OVERSIZED O (4) 4" [100] PE REFRIG IN O REFRIG OL (4) 4" [100] PE REFRIG IN O PE REFRIG OL (4) 4" [100] PE REFRIG IN O PE RE	2'-6 3/4" [781] * 5'-9 5/8" [1768]  14'-4" [4369]  9'-11" [3023] * 8'-6 3/8" [2600]	2"	1'-6 1/4"
	### FACE B  SHIPPING WEIGHT 62990 lbs+ [28575] kg+	OPERATING WEIGHT 77610 lbs+ [35205] kg+ HEAVIEST SECTION WEIGHT 23850 lbs+ [10820] kg+	NO OF CHIRPHIA OF CTIONS	DRAWN BY: JLG