IOTES: . (M)- FAN MOTOR LOCATION . HEAVIEST SECTION IS UPPER SECTION . MPT DENOTES MALE PIPE THREAD . FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES PLAINGE PE DENOTES PLAIN END . +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS)	TE 6/17/2025
ACCESS DOOR  BFW DENOTES MALE PIPE THREAD  BFW DENOTES BEVELED FOR WELDING  GVD DENOTES GROOVED  FLG DENOTES FLANGE  PE DENOTES PLAIN END  +UNIT WEIGHT DOES NOT INCLUDE  ACCESSORIES (SEE ACCESSORY DRAWINGS)  MAKE-UP WATER PRESSURE  20 psi MIN [137 kPa], 50 psi MAX [344 kPa]  *-APPROXIMATE DIMENSIONS DO NOT USE  FOR PRE-FABRICATION OF CONNECTING  PIPING	
DRAIN BY OTHERS. 3. 3/4" [19MM] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 9. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm]  7" [ 178]	<u>CE D</u>
(4) 4" [100] BFW FLUID IN (4) 4" [100] BFW FLUID OUT FLU	