## EVAPCO, INC. UNIT MODEL # DATE SERIAL # SCALE **CLOSED CIRCUIT COOLER** NTS W2122408-ERD-SRL 7/8/2025 eco-ATWB 9-5M14 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 71 7/8 BOTTOM 71 7/8 3. MPT DENOTES MALE PIPE THREAD **OUTLET** FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING (M) 24 1/8 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT 11'-10" 6. THE SPRAY PUMP SHOULD BE SIZED FOR 1600 GPM AND 2.5 PSIG AT THE INLET CONNECTION 7. \*- APPROXIMATE DIMENSIONS DO NOT USE FACE 1 FOR PRE-FABRICATION OF CONNECTING **PIPING** 24'-2" FACE 2 **PLAN VIEW** 36 3/4 (M) ACCESS M ACCESS DOOR 36 3/4 128 5/8 1 5/8 -- 1 5/8 6 FPT 6 FPT FLUID IN (4) 4 BFW (2) 1/2 FPT (2) 1/2 FPT 16'-10 3/4" INLET INLET 10 3/8 -30 3/4 **VENT VENT** (4) 4 BFW FLUID OUT 5 1/4 74 1/8 11'-10" 24'-2" FACE 1 FACE 2 NO. OF SHIPPING SECTIONS SHIPPING OPERATING HEAVIEST SECTION lbs.+ 35900 47620 lbs. 15400 lbs 4 WEIGHT WEIGHT WEIGHT