NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES FEMALE PIPE THREAD BFW DENOTES FLANGE PE DENOTES FLANGE PE DENOTES PLANGE PE DENOTES PLANGE PE DENOTES PLANGE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE  WB3TM1808-DRC-ST  WB3TM1808-DRC-ST  WB3TM1808-DRC-ST  SERIAL #  FACE B	DATE 8/26/2025
1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) FACE B	
20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm]	CE D
2'-6 3/4" * (2) 4' 100) PE REFRIG IN REFRIG OUT (43.2)8"	