UNIT	CLOSED CIRCUIT C	OOLER	EVADCO TNC EVADCO WB324	408-DRC-ST REV
MODEL #	ATWB 24-4M14	SCALE NTS	EVAPCO, INC. EVAPCO SERIAL #	DATE <sub>12/13/2025</sub>
2. HÉAV 3. MPT [ FPT D BFW I GVD I FLG D PE DE 4. +UNIT ACCE 5. MAKE 20 psi 6. *-APP FOR F PIPIN: 7. 3/4" [1 RECO	AN MOTOR LOCATION IEST SECTION IS UPPER S DENOTES MALE PIPE THRI DENOTES FEMALE PIPE TH DENOTES BEVELED FOR V DENOTES GROOVED DENOTES FLANGE ENOTES PLAIN END TWEIGHT DOES NOT INCL ESSORIES (SEE ACCESSOF E-UP WATER PRESSURE MIN [137 kPa], 50 psi MAX   ROXIMATE DIMENSIONS D PRE-FABRICATION OF CON	EAD IREAD VELDING  UDE RY DRAWINGS)  [344 kPa] IO NOT USE INECTING  LES. REFER TO RT DRAWING.	FACE B PLAN VIEW FACE A	FACE D
	<del></del>		[ 178] 1'-3 1/4" [ 387 ]	<del></del>
	2-6-3/4 * [781] (4) 4"	[100] BFW FLUID IN FLUID OUT	- 5'-9 1/4" * 3'-3/8" * 9'-1/8" [2748]  (4) 4' [100] BFW (4) 4' [100] BFW (4) 4' [100] BFW (5) (4) 4' [100] BFW (6) (6) (6) (6) (6) (6) (6) (6) (6) (6)	

1'-5" [ 433]

> 1'-6 1/2" [ 470 ]

4'-8" [ 1422]

11'-4 3/4" [ 3473] 11'-5 3/4" [ 3499] 11'-10" \_\_ [ 3607]

2'-1 1/4" [ 643 ]

> 3 5/8" \_ [ 92]

(2) 3" [80] MPT -OVERFLOW (2) 2" [50] MPT — MAKE-UP

(2) 3" [80] MPT <sup>J</sup> DRAIN

> 5 1/8" [ 130 ]

24'-1 1/8" [7344]