UNIT								WB3241412-DRC-ST		
MODEL #	ATWB 24-6L14	^{SCALE} NTS	EVAP	.U, 11	1 C.		SERIAL #		DATE 9/10/2025	
2. HÉAVIES 3. MPT DEN FPT DEN FPT DEN BFW DEN GVD DEN FLG DEN PE DENO 4. +UNIT WE ACCESSO 5. MAKE-UP 20 psi MIN 6. *-APPRO FOR PRE- PIPING 7. 3/4" [19mr RECOMM 8. DIMENSIO	MOTOR LOCATION I SECTION IS UPPE OTES MALE PIPE TO OTES FEMALE PIPE OTES GROOVED OTES FLANGE TES PLAIN END EIGHT DOES NOT IN ORIES (SEE ACCESS WATER PRESSURI I [137 kPa], 50 psi M. KIMATE DIMENSION FABRICATION OF CO IMMILIARY IN DIA. MOUNTING I ENDED STEEL SUP ONS LISTED AS FOL ENGLISH FT-IN METRIC [mm]	HREAD THREAD R WELDING ICLUDE SORY DRAWINGS) E AX [344 kPa] S DO NOT USE CONNECTING HOLES. REFER TO PORT DRAWING.			<u>P</u>	FACE B			ACE D	
l					7" [178]	1'-3 1/4" [387]	<u>F/</u>	ACE A		
	3'-11 3/4" * [1213] * 2'-1 1/4" [643]	(4) 4" [100] BFW FLUID II (4) 4" [100] BFW FLUID OI (2) 2" [50] MPI MAKE-UF (2) 3" [80] M DRA 5 1/4	UT (4) 4" [100] BFW FLUID OUT O O O O O O O O O O O O O O O O O O	3'-3/8" * [924] * 6" * [154] *	10'-5 1/8" [3180] 17'-7 3/8 [5369] 7'-2 1/4" [2189] 1'-5" [433]	(4) 1/2" [15] FPT VENT	(h)			
	-		24'-1 1/8" [7344]			1'-6 1/2" - [470]		-11 3/4"		
	FACE B									
SHIPPING WEIGHT	48780 lbs-	+ [22130] kg+	OPERATING 74720 lbs+ [338	95] kg+	HEAVIEST SECTION WEIGHT	21330 lbs+ [9680] kg+	NO. OF	SHIPPING SECTIONS 4	DRAWN BY: SLR	