NOTES  NO	CLOSED CIRCUIT COOLER	EVADOO TRIC EVALUEO * WB3TM2412-DRC-	-ST REV
1. OMF FAN MOTOR LOCATION 12  1. PARKETS RESCRICTION 15  1. PROVIDES RESOURCE PRICE RESCRICTION 15  1. PROVIDES REALINE EMPTERHEAD  1. PROVIDES REALINE EMPTER	ODEL # ATWB 10-6M24 SCALE NTS	EVAPCO, INC. SERIAL #	DATE 8/31/2025
1-3 1/4"  - 4-9" * 2-6 3/8" * 1772] * 10-5 1/8"  (a) 42 (100) BFW   FLUID IN   16-7 3/8"   (a) 42 (100) BFW   (a) 12 1/15   (b) 1/4"   (a) 1/2 1/15   (b) 1/2 1/15   (b) 1/2 1/15   (c) 1/4"   (a) 1/2 1/15   (b) 1/2 1/15   (c) 1/2 1/2   (c) 1/2   (c) 1/2 1/2   (	1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN	FACE B PLAN VIEW  FACE A  FACE A	
FACE B	(2) 2" [50] MPT (4) 4" [100] BFW (2) 2" [50] MPT (3) 3 5/8" (2) 3" [80] MPT (3) 1/4" (108] (1) 292] (2) 3" [80] MPT (108] (3) 4 1/4" (108] (3) 5'-11 3/4" (108] (3) 9'-9 3/4" (2991]	2'-6 3/8" * [ 772] *  10'-5 1/8" [ 3180]  16'-7 3/8" [ 5064]	1'-5" [432]