NOTES: 1. (M)- FAN MOTOR LOCATION 2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING 5. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT IN [METRIC] [mm] USE FOR PRE-FABRICATION OF CONNECTING PIPING FACE D FACE D	UNIT	CLOSED CIRCUIT CO	DOLER		SCO TI	NC EV	unco "	DWG. #	WV051210-DRC-ST	REV
1. (M) FAN MOTOR LOCATION 2. MPT DENOTES REALE PIPE THREAD PEPT DENOTES PLANE PERT DENOTES PLANE P	MODEL #	eco-LRWB 5-5L12	SCALE NTS	EVAF	7 CO, 11	NC.		SERIAL #		DATE 7/17/2025
#" [100] BFW FLUID IN	2. MPT DE FPT DE BFW DI GVD DI FLG DE PE DEN 3. +UNIT \ ACCES 4. 3/4" [19 RECOM 5. DIMEN: 6. * - APP USE FC 7. MAKE-I	ENOTES MALE PIPE THREATHORDES FEMALE PIPE THREATHORDES FEMALE PIPE THREATHORDES BEVELED FOR WE ENOTES FLANGE NOTES FLANGE NOTES PLAIN END WEIGHT DOES NOT INCLUITSORIES (SEE ACCESSORY IMM] DIA. MOUNTING HOLE IMMENDED STEEL SUPPORT SIONS LISTED AS FOLLOW ROXIMATE DIMENSIONS DO OR PRE-FABRICATION OF CUP WATER PRESSURE	EAD ELDING DE (DRAWINGS) ES. REFER TO F DRAWING ES: ENGLISH FT IN [METRIC] [mm] O NOT CONNECTING PIPING				FACE C			FACE D
4" [100] BFW FLUID IN FLUID OUT [15] [1905] 4" [100] BFW FLUID OUT [15] [1905] 4" [100] BFW FLUID OUT [15] [1905] 3" [80] MPT OVERFLOW 2" [5] [1907] DRAIN [1540] 4" [100] BFW FLUID OUT [15] [1905] 4" [100] BFW FLUID OUT [15] [15] [15] [15] [15] [15] [15] [15]		_ 2'-6 3/8" ∗ - -	-			b :		/8"	-	
4" [100] BFW FLUID OUT FLU		00] BFW	•	4'-11 1/2"	1// FF	2" [15] PT VENT		-	[1905]	•
3 1/4" TYP. — DOOR 3 1/4" TYP. — DOOR 3" [80] MPT				* 7'-11 3/4" [2432]			ACCESS &			6'-7 3/4" [2026]
OVERFLOW 2" [50] MPT DRAIN 5'-5/8" [1540] ACCESS DOOR 1'-8 7/8" [1349] 1'-1 5/8" [15553] FACE A	3 [M	3'-1/4" [919]			DOOR			
FACE A	0	VERFLOW [50] MPT	1'-8 7/8" [530]		1'-1 5/8"			/8"	- 1" [25] MPT MAKE-UP	ACCESS DOOR
		[1540					FACE A			