NOTES:  1. The Tark MOTOR LOCATION  2. MAY DENOTES MALE PIPE THREAD  BRY DENOTES REVELED FOR WELDING  GVD DENOTES REVELED FOR WELDING  FACE C	UNIT	CLOSED CIRCUIT CO	CLOSED CIRCUIT COOLER		EVADOO TNO EVOIDOO				DWG. # WV051210-DRC-ST	
PRIVE DENOTES PROVED  FACE C  FOUND ENOTES OR SHOULD FOR MININGS  1. WHIT WEIGHT DOES NOT INCLUE  ACCESSORIES (SEE ACCESSORY DRAWINGS)  3. WHIT WEIGHT DOES NOT INCLUE  ACCESSORIES (SEE ACCESSORY DRAWINGS)  5. DIRECTOR OF THE PRIVATE OF THE PRIVAT	MODEL #	eco-LRWB 5-5M12	SCALE NTS	EVA		INC.		SERIAL	#	DATE 7/17/2025
4" [100] BFW FLUID IN FLUID OUT [1513] 7'-11 3/4" ACCESS DOOR 1'-8 1/8" [194] 1'-8 1/8" [195] 1'-8 1/8" ACCESS DOOR 1'-15 3/4" [124] 1'-15 3/4" ACCESS DOOR 1'-1	1. (M)- FA 2. MPT DI FPT DE BFW D GVD DI FLG DE PE DEI 3. +UNIT ACCES 4. 3/4" [19 RECOM 5. DIMEN 6. * - APP USE FC 7. MAKE-I	ENOTES MALE PIPE THREA ENOTES FEMALE PIPE THREA ENOTES BEVELED FOR WE ENOTES GROOVED ENOTES FLANGE NOTES PLAIN END WEIGHT DOES NOT INCLUDES (SEE ACCESSORY DIMM) DIA. MOUNTING HOLE MENDED STEEL SUPPORT SIONS LISTED AS FOLLOWS ROXIMATE DIMENSIONS DOES PRE-FABRICATION OF CUP WATER PRESSURE	EAD ELDING  DE DRAWINGS) S. REFER TO DRAWING S: ENGLISH FT IN [METRIC] [mm] O NOT ONNECTING PIPING				18'-2	55/8"		FACE D
	4" [ Fl 3" [ ;	00] BFW FLUID IN 100] BFW UID OUT 1/4" TYP. 1/83" TYP. 1/983 TYP.	2 5/8" [67] 4 7/8" [124]	* 7'-11 3/4" 1/4" * 133] 3'-1/4" [ 919 ]		£ 1/2" [15] FPT VENT	11'-5 3/4" [ 3499 ]  18'-2 [ 55			ACCESS