NOTES: 1. (VP) FMM MOTOR LOCATION BWY DENOTES BEVELED FOR WEIDING GVD DENOTES FEMALE PIPE THREAD BWY DENOTES GROOVED 1. GO ENOTES FLANCE 1. VIAIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEMANTE ORAVINIOS ACCESSORIES (SEE SEMANTE ORAVINIOS 1. MAKE UP WATER PRESSURE-20 ppi MIN, 50 pm MAX (SEE) 1. (VP) FMM MOTOR LOCATION FACE B 1. (1905) 1. (1	NOTES: 1. (M) FAN MOTOR LOCATION 2. MPT DENOTES MALE PIPE THREAD PPT DENOTES MALE PIPE THREAD BPW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLO DENOTES NOT INCLUDE ACCESSORIES (SEE SEPARATE DEAWINGS FOR ACCESSORIES) 4. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STELL SUPPORT DRAWING 5. MAKE-UP WATER PRESSURE-20 psi MIN, 50 psi MAX 6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] MM FACE A 6" [150] BFW/GVD INLET 6" [150] BFW/GVD INLET 6" [150] BFW/GVD INLET	PACE D
PHY DENOTES BEVALED FOR WELDING GNO DENOTES BEVALED FOR WELDING GNO DENOTES GROUND A CONSTRUCT OF MACHINE A CACESSORIES (SEE SEPRADATE DRAWINGS FOR ACCESSORIES) 4. 3/4* DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING 50 pt MX 50 pt MX 50 pt MX 6-3/8* INEETIC J MM FACE A PLAN VIEW 6-7.3/4* 6-7.3/4 1905 1 1-8.3/8* ACCESS DOOR 1-7.3/4 1-8.3/8* ACCESS DOOR 1-8.3/8* 1-8.3/8* ACCESS DOOR 1-7.3/4 1-8.3/8* ACCESS DOOR 1-7.3/4 1-8.3/8* ACCESS DOOR 1-7.3/4 1-8.3/8* ACCESS DOOR 1-8.3/8*	1. (M) FAM MOTOR LOCATION 2. MFD TENDETS MALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES GROOVED FLG DENOTES SEVELED FOR WELDING ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. MAKE-UP WATER PRESSURE-20 psi MIN, 50 psi MAX 6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN IMETRIC] MM FACE A FACE A	FACE D
6'-3/8" [1840] ACCESS DOOR 6'-73/4" [919] ACCESS DOOR 6'-73/4" [2026] ACCESS DOOR 6'-73/4" [2026]	INLET [76]	
57/8" 51/2" 8'-0" 23/4" [35] 8'-71/2" [2629] 11'-55/8" [359] 18'-25/8" [5553] FACE B	6'-3/8" [1840] 8'-2-7/8" [2511] ACCESS DOOR 3" [75] MPT OVERFLOW OUTLET 1"-8 1/8"	6'-7 3/4" [2026]