COOLING TOWER			T	EVAPCO, INC. Evapeo					AX142417-DR	A-ST	REV.
MODEL #	(S 14-19O24	SCALE		EVAPC	J, II	VC.		SERIAL	#		DATE 9/5/2025
2. HEAVIEST S 3. MPT DENOTE FPT DENOTE BFW DENOTE GVD DENOTE 4. +UNIT WEIG ACCESSORI 5. MAKE-UP WA 20 psi MIN [1: 6. 3/4" DIA. MOI RECOMMEN	TOR LOCATION ECTION IS UPPER SECTIO ES MALE PIPE THREAD ES FEMALE PIPE THREAD ES BEVELED FOR WELDIN ES GROOVED HT DOES NOT INCLUDE ES (SEE ACCESSORY DRA ATER PRESSURE 37 kPa], 50 psi MAX [344 kF UNTING HOLES. REFER TO DED STEEL SUPPORT DRA S LISTED AS FOLLOWS: EN	ng Awings) Pa] O Awing.		PLAN VIEW	6'-11 5/8" [2124] 		FACE C ACCESS DOO	•		(2) 1	ACE D LO" [250] ASME BOLT PATTERN ET
			7" [178	317			FACE A	_			
				9'-4 3/8" 2855]				<u> </u>		∕– 4" [10 OVER	00] FPT FLOW
				19'-4" [5893])] MPT
			[9'-11 5/8"	 		ACCESS DOOR			∕-4" [1(DRAI	00] FPT N
				<u> </u>	V V V				10'-3"		
	13'- [424	.11 1/4" 8] E B	-		3"	14" [350	D] BFW/GVD — OUTLET 24'-9" [7544]		10'-3" [3124] 11'-1" [3378] 2'-4 1/2"		
SHIPPING WEIGHT	21480 lbs+ [9745] kg	+	OPERATING WEIGHT	48130 lbs+ [21835] k	(g+	HEAVIEST SECTION WEIGHT	12120 lbs+ [5500] kg+	⊢ NC). OF SHIPPING SECTIONS	2	DRAWN BY: AWT