NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BFV DENOTES FEMALE PIPE THREAD BFV DENOTES FEMALE PIPE THREAD BFV DENOTES REVELED FOR WELDING GVO DENOTES REVELED FOR WELDING ACCESSORIES (SEE ACCESSORY DRAWINGS) ACCESSORIES (SEE ACCESS	DWG. # WB3TM1808-DRC-ST REV		UNIT CONDENSER
NOTES: 1. (M) - FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BPV DENOTES GROVED BPV DENOTES GROVED BPV DENOTES GROVED BPV DENOTES GROVED BPV DENOTES PLAIN END 4. HUNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-LIP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm] FACE A FACE B PLAN VIEW FACE B FACE B PLAN VIEW FACE B PLAN VIEW FACE B FACE B FACE B FACE B PLAN VIEW FACE B FACE B FACE B FACE B PLAN VIEW FACE B F	EVAPCO, INC. evapco serial # DATE 7/13/2025	SCALE NTS	MODEL #
2'-6 3/4" * (2) 4" [100] PE REFRIG IN REFRIG OUT (2) 4" [100] PE REFRIG OUT	FACE B PLAN VIEW FACE D	AD READ ELDING DE Y DRAWINGS) A44 kPa] D NOT USE NECTING ES. REFER TO IT DRAWING.	1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECT 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD FPT DENOTES SEVELED FOR WELE GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DE 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344] 6. *-APPROXIMATE DIMENSIONS DO NO FOR PRE-FABRICATION OF CONNEC PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. RECOMMENDED STEEL SUPPORT D 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN
2" [50] MPT	* (9'-1/8" (2748) * (4328) * (1-3-31/4" (1580) * (1-5-1/4" (1580) 11-5-1/4" (15486)	PE REFRIG IN REFRIG OUT 3/4" 9'-9 3/4" [2991]	2'-6 3/4" * [781] * (2) 4" [100] PE 2" [50] MPT MAKE-UP 2'-1 1/4" [643] 3" [80] MPT DRAIN 3 5/8" 4 1/4" [108] 5'-11 3/4" [1822]