NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES FEMALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING FACE B	DATE 8/21/2025
1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD BFW DENOTES BEALE PIPE THREAD BFW DENOTES GROOVED FIG DENOTES GROOVED FIG DENOTES FLANGE PE DENOTES FLANGE 20 psi Min [137 kPa], 50 psi Max [344 kPa] 6. "APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWINGS. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm] FACE D FACE A	
7"	
[387]	
<u> </u>	
2'-6 3/4" * (4) 4" [100] PE REFRIG IN REFRIG IN REFRIG OUT (4) 4" [100] PE REFRIG OUT (5) 4 4" [100] PE REFRIG OUT (6) 4" [154] * [2189]	
2'-1 1/4" [643] (2) 2" [50] MPT MAKE-UP (2) 3" [80] MPT OVERFLOW (2) 3" [80] MPT OVERFLOW (3473] (1'-6 1/2" (4'-8" (1422) (1'-5" (433) (1'-6 1/2" (470) (1'-6 1/2" (470)	
FACE B SHIPPING WEIGHT 46240 lbs+ [20975] kg+ OPERATING WEIGHT 62240 lbs+ [28235] kg+ HEAVIEST SECTION WEIGHT 20060 lbs+ [9100] kg+ NO. OF SHIPPING SECTIONS 4 DRAWLIGHT AND CONTROL OF SHIPPING SECTIONS 4 DRAWLIGHT NO. OF SHIPPING SE	l