NIT	COOLING TOW	ER	EV/ADCC	TNIC	evapco	DWG. #	T3124024-DRB-ST	REV.
ODEL #	AT 212-2M40	SCALE NTS	EVAPCO	), INC.	evapco	SERIAL #		DATE 8/26/2025
. HEAVIES . MPT DEN FPT DEN BFW DEI GVD DEN FLG DEN . +UNIT W ACCESS . MAKE-UI 20 psi MI . 3/4" [19M RECOME DIMENSI	MOTOR LOCATION IT SECTION IS UPPER SE IOTES MALE PIPE THRE/ OTES FEMALE PIPE THRE/ OTES BEVELED FOR WI IOTES GROOVED OTES FLANGE EIGHT DOES NOT INCLU ORIES (SEE ACCESSOR) P WATER PRESSURE N [137 KPa], 50 psi MAX [3 IM] DIA. MOUNTING HOLI ENDED STEEL SUPPORT ONS LISTED AS FOLLOV GLISH FT-IN ETRIC] [mm]	AD EAD ELDING  DE / DRAWINGS)  44 kPa] ES. REFER TO DRAWING.	FACE B PLAN VIEW		ACCESS DOOR	CE C	ACCESS DOOR	FACE D
					<u>FA</u>	CE A		
T==		[ 178 ]	1'-3 1/4" _ [ 387 ]			1		
		2" [51] 8'-4" [2540]	<del> </del>	10'-0"	(M)		(M)	
88	888888888888888888888888888888888888	15'-6 1/	4" ]	888884 8888884 88888	SH 15383830 15383830 15383830	B38388 B38388 B383	(2) 10" [250] BFW/GVD INLET	Ţ
		7'-2 1/4" [ 2191 ]	10'-1" [3073]					
		1 1	2'-1 1/4"	1 <u>9</u>	9'-3" 867 ]	(2) 3" [80] FPT OVERFLOW (2) 3" [80] FPT DRAIN (2) 2" [50] MPT MAKE-UP	(2) 10" [250] BFW/GVD OUTLET	
-	11'-10" [ 3607 ] FACE B	3/8"	[92]			2 1/2"  -2 1/2"  -2 1/2"  -2256 ]		