EVAPCO, INC. FACE PLAN MOTOR LOCATION PROPERTY											
NOTES: 1. (M) FAN MOTOR LOCATION 2. HEAVEST SECTION IS FANCASING SECTION 3. MET DENOTES MALE PIPET PRIVATE GVD DENOTES GROOVED 1. (D) FAN MOTOR LOCATION 3. MET DENOTES MALE PIPET PRIVATE GVD DENOTES GROOVED 1. (D) FAN SERVE LED FOR WELDING GVD DENOTES GROOVED 1. (D) FAN SERVE LED FOR WELDING GVD DENOTES GROOVED 1. (D) FAN SERVE LED FOR WELDING GVD DENOTES (SEC ACCESSORY DRAWINGS) 5. 34" [MMM] MO MOUNTING HEAVE 1. (D) FAN SERVE LED FOR WELDING ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. 34" [MMM] MO MOUNTING HEAVE 1. (D) MEMORISM SISTED AS FOLLOWS 1. (D) M	COOLING TOWER MODEL# SCALE			FVADCO INC evapco			T4283624-DRA-ST			-	
1. (M. FAM MOTOR LOCATION) 2. HAVIESTS ECTION IS FANCASING SECTION 3. MET DENOTES MALE PIPE THERAD 3. MET DENOTES MALE PIPE THERAD 6. PER PENDENCE STORY PROMISES 6. DIMENSIONS LISTED AS FALSONG MINISTRATION 6. DIMENSIONS LISTED AS FALSONG MINISTRATION 6. DIMENSIONS LISTED AS FALSONG MINISTRATION 7. MAKE-UP WATER PIPESSURE 7. JUNE SON COULLIZERS SUPPLIED BY 8. OTHERS 8. PAN EQUALIZER RIPPOLE IS 111-10 38° [9616] 7. MAKE-UP WATER PIPESSURE 8. OTHERS 8.				S	LVAPCO, INC.			SERIAL#			
11-5 1/4" [438] 2 1/8" 2 1/8" [54] 17-8 3/8" [5394] 8-3 1/4" [2521] 8-3 1/4" [350] 9 1/8" [232] 11-3 3/4" [348] 9 1/8" [232] 11-3 3/8" [350] 9 1/8" [232] 11-3 3/8" [350] 13-2 1/4" (4) 12" [300] 9 1/8" [232] 13-8 1/8" 13-8 1/8" [4] 3" [350] 9 1/8" [232] 13-8 1/8" 13-8 1/8" [548] 13-8 1/8" [54] 11-3 3/4" [54	1. (M)- FA 2. HEAVI 3. MPT D FPT DI BFW D GVD D FLG DI 4. +UNIT ACCES 5. 3/4" [19 REFER SUPPO 6. DIMEN ENO [ME 7. MAKE- 20 psi 8. PAN FL EVAPC BY OTH 9. PAN EC	EST SECTION IS FAN/CAS ENOTES MALE PIPE THRE ENOTES FEMALE PIPE TH DENOTES BEVELED FOR V DENOTES GROOVED ENOTES FLANGE WEIGHT DOES NOT INCL SSORIES (SEE ACCESSOF MM] DIA. MOUNTING HOL R TO RECOMMENDED STE DRT DRAWING ISIONS LISTED AS FOLLO GLISH FT-IN ETRIC] [mm] LUP WATER PRESSURE MIN [137 kPa], 50 psi MAX LUME BOX EQUALIZERS S DO PAN EQUALIZER PIPING HERS. QUALIZER NIPPLE IS 11'-16	EAD HREAD WELDING LUDE RY DRAWIN LES. EEL DWS: [344 kPa] GUPPLIED B G IS SUPPL	GS) Y IED			(4) ACCESS DOOR				FACE D
FACE A	(4) 14 BFV OI (4) 3" OVE	[34] [350] [37] [350] [37] [350] [37] [350]	11'-6" [3505] 13'-2 1/4" [4020] 13'-6 1/8" [4118] 13'-7" [4140] 13'-11 1/4"	8	1'-5 1/8" [2873] 2 1/8"	11'-3 3/4" [344	9 1/8" [23 1 3/4 18'-0"	32] 32] 39'-7	ACCESS DOOR ACCESS DOOR (4) 12" [300] BFW/GVD EQUALIZER (SEE NOTE #9) [1092]		
	SHIPPING		1	OPERATING	402060 lbo / [46705] l/a :	HEAVIEST SECTION	10040 lbo : [4005] kg :		UBBUIG OFFICIA	RAWN BY:	TDQ