CONDENSER  EVAPCO, INC. EVAPCO SERIAL #  SERIAL #	REV	-
PMRC-1296 SCALE NTS LVAPCO, LINC. SERIAL#	DATE: 8/9	9/2025
NOTES:  1. (M)- FAN MOTOR LOCATION.  2. MPT DENOTES MALE PIPE THREAD BPV DENOTES BEWLELD FOR WELDING GVD DENOTES SERVLED FOR WELDING GVD DENOTES HEALE PIPE THREAD BPW DENOTES BEWLED FOR WELDING GVD DENOTES FLANGE PE DENOTES PLAIN END  3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS). 4.3/4" [Smmill DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [34 kPa] MAX. 6. DIMENSIONS LISTED AS FOLLOWS: ENSLISH FT-IN [METRIC] [mm] 7. *- APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING.		FACE D
3'-0 7/8" * 5'-8 5/8" *		
OVERSIZED ACCESS DOORS 3"80] MPT DRAIN 11-8" [508] 3 7/8" [98] 3 7/8" [98]  11-10 3/8" [1534] 11-10 3/8" [1534] 11-10 3/8" [1534] 11-10 3/8" [1534] 11-10 3/8" [1534] 11-10 3/8" [1538] 11-10 3/8" [1508] 3 7/8" [98]  11-10 3/8" [100] PE REFRIG N 3'-3 1/4" [997] * 6'-6 1/8" [1984] 6'-6 1/8" [1984]  8'-6 3/8" [2600]  11-8" [508] 11-8" [508] 11-8" [508] 11-8" [508]		1'-6 1/4" [464]
<u>FACE B</u>	RAWN BY:	ILG