UNIT CONDENSER			<u> </u>				REV -
IODEL#		SCALE NTS	⊢ EV/	APCO, INC	evapco	CEWRTM3606-DRA-ST	DATE: 12/16/2025
NOTES: 1. (M)- FAN MOTOR LOCATION. 2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS). 4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [344 kPa] MAX. 6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] [mm] 7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING.				FACE D FACE D FACE A			
DC 2"[50] I MAKE	[772] [14 (4) 4" [100] PE (4) 4" [100] PE (5) PE (6) 4" [100] PE (7) PE (8) PE (9) PE (10)	9" * 448] OREFRIG IN REFRIG OUT	13'-7 1/2" [4153]	1 1/8" [1553] 3'-6 3/8" [2600] 1'-8" [508]		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1'-6 1/4" [464]

HEAVIEST SECTION WEIGHT **FACE A**

15660 lbs+ [7105] kg+

NO. OF SHIPPING SECTIONS

DRAWN BY:

JLG

9'-9 3/4" [2991] **FACE B**

45640 lbs+ [20705] kg+

OPERATING WEIGHT

57460 lbs+ [26065] kg+

SHIPPING WEIGHT