| CONDENSER  |   |                  | EVAPCO, INC.                       |                  |                         |                  |                   | CEWR123612-DRA-ST          | REV       | -                  |
|--|---|------------------|------------------------------------|------------------|-------------------------|------------------|-------------------|----------------------------|-----------|--------------------|
| eco-PMRC-  | 2168 SCALE N                                      | TS               | E V                                | APCO,            | TIAC.                   |                  |                   | SERIAL #                   | DATE:     | 9/10/2025          |
| NOTES:  1. (M)- FAN MOTOR LOCATION.  2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END  3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS).  4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING.  5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [344 kPa] MAX.  6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] [mm] 7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING. |   |                  | FACE B PLAN VIEW                   |                  |                         |                  | FACE C            |                            |           | FACE D             |
|  |   |                  | FACE A                             |                  |                         |                  |                   |                            |           |                    |
| 3'-0 7/8" *<br>[937]   | 5'-8 5/8" *<br>[1743]                             |                  | <u> </u>                           |                  |                         |                  |                   |                            |           |                    |
| OVERSIZED — ACCESS   | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0             | 3'-11 3          | 3/4" [1213] *                      | 7'-2 5/8" [2200] |                         |                  |                   |                            |           |                    |
| 3"[80] MPT 5 1/8"<br>MAKE UP [130]<br>3"[80] MPT DRAIN  2'-5"[737]   |   |                  | 15'-9" [48<br> <br> <br>  [3023] * | 8'-6 3/8" [2600] | (M)                     |                  |                   |                            |           | 3                  |
| 3 7/8" [98]  | 4 3/4"<br>[121]<br>0 3/8"<br>1534]<br>11'-10 3/8" | MPT<br>DW        |                                    | 1'-8"<br>[508]   | -                       |                  | 36'-2"<br>[11024] |                            | - -       | 1'-6 1/4"<br>[464] |
| ļ <del>.</del>   | [3616]  |                  |                                    |                  |                         |                  |                   |                            |           |                    |
| SHIPPING 2000 "  | FACE B  | OPERATING        | FRATING 00070 II 1440401           |                  |                         | 00470 "          | FACE A            | NO OF SHIPPING SECTIONS    | DRAWN BY: | JLG                |
| SHIPPING 83880 lbs   | + [38050] kg+                                     | OPERATING WEIGHT | 99070 I                            | lbs+ [44940] kg+ | HEAVIEST SECTION WEIGHT | 33470 lbs+ [1518 | გე kg+            | NO. OF SHIPPING SECTIONS 3 | 1         | JLG                |