NOTES:  1. (M) FAN MOTOR LOCATION  2. HEAVIEST SECTION IS UPPER SECTION  3. MPT DENOTES MALE PIPE THREAD BFV DENOTES FEMALE PIPE THREAD  4. HUNIT WEIGHT DOES NOT INCLUDE ACCESSORES PLAIN END  4. HUNIT WEIGHT DOES NOT INCLUDE ACCESSORES FEMALE PIPE THREAD  5. MANK-UP WATER PRESSURE 20 psi Mini (137 KPa), 30 psi MAX (344 KPa) BFACE B  PLAN VIEW  FACE D  FACE A  FACE A  FACE A		WB3TM1808-	10 31
1. (M)- FAN MOTOR LOCATION 3. MPT DENOTES MALE PIPE THREAD BPT DENOTES FEMALE PIPE THREAD BPT WENDTES FEMALE PIPE THREAD BPW DENOTES GROOVED FLIC DENOTES HANGE FED ENOTES PLAIN END 4. **JUIT WEIGHT DOES NOT INCLUDE ACCESSOR'S FEACE SORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 2.0 psi Min [73 rps], 50 psi MAX [344 kps] 6. **AOR MINKHANTE PRESSURE PIPING 7. 344" [19mm] DIA MOUNTING HOLES REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS:  ENCLISH FT-IN METRIC [mm]  FACE A	-# ATC-XC611E SCALE NTS	VAPCO, INC. SERIAL #	DATE 8/26/2025
2'-6 3/8" *  2'-6 3/4" *  (2) 4" [100] PE REFRIG IN  14'-2 3/8" [2748]	M)- FAN MOTOR LOCATION HEAVIEST SECTION IS UPPER SECTION MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES FLANGE PE DENOTES PLAIN END -UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) MAKE-UP WATER PRESSURE 10 psi MIN [137 kPa], 50 psi MAX [344 kPa] -APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 1/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN	FACE B PLAN VIEW	FACE D
2" [50] MPT	2'-6 3/4" *  (2) 4" [100] PE  REFRIG IN  REFRIG OUT  2" [50] MPT  MAKE-UP  2" [54]  2"-1 1/4"  [643]  3" [80] MPT  DRAIN  3 5/8"  3" [80] MPT  OVERFLOW  4 1/4"  [108]  5'-11 3/4"  [1822]  9'-9 3/4"  [2991]	1-3 1/4" [387]  1-4-2 3/8" [4328]  -2 1/4" 1580]  1-5 1/4" [438]	