UNIT	COOLING TOW		EVAPCO, INC. EVOPCO SER			vg. # T4142448-DRA-ST	REV.
MODEL #	AT 114-4P24	SCALE NTS	EVAP	CO, INC.	SE	RIAL #	DATE 7/17/2025
2. HÉAVIE 3. MPT DE FPT DE BFW DI GVD DE FLG DE PE DEN 4. +UNIT V ACCES 5. MAKE-U 20 psi M 6. 3/4" [19 REFER DRAWII 7. DIMENS	N MOTOR LOCATION EST SECTION IS UPPER S ENOTES MALE PIPE THRE NOTES FEMALE PIPE TH ENOTES BEVELED FOR W ENOTES GROOVED ENOTES PLAIN END WEIGHT DOES NOT INCLU SORIES (SEE ACCESSOR JP WATER PRESSURE MIN [137 kPa], 50 psi MAX [MM] DIA. MOUNTING HOL TO RECOMMENDED STE NG SIONS LISTED AS FOLLOW GLISH FT-IN TRIC] [mm]	AD READ /ELDING JDE Y DRAWINGS) 344 kPa] ES. EL SUPPORT		FACE PLAN VIEV		ACCESS DOOR	ACE D
			7" [178]	1'-5 1/4" [438]			
			11'-2 1/4" [3410]				
		_ - [2 5	[3410] [51] 19'-5 1/2" [5931]		11'-10 1/2"	14" [350] BFW/GVD INLET	
			8'-3 1/4" [2521]	13'-3 3/4" [4058]			
			<u>'</u>	2'-2" [660] 1'-5 3/8" [229] -	4" [100] FPT OVERLOW 4" [100] FPT DRAIN -6'-1/4" [1835]	14" [350] BFW/GVD OUTLET	
	13'-11 1/4' [4248] FACE B		3/8" [9]	9" [229]	11'-10 1/2" 23' 23' FAC		
SHIPPING WEIGHT	19260 lbs+ [8	740] kg+	OPERATING 35540 lbs+ [16125] kg+ HEAVIEST SECTION WEIGHT	13420 lbs+ [6090] kg+	NO. OF SHIPPING SECTIONS 2	DRAWN BY: MER