CLOSED CIRCUIT COO	LER	EVADOS TAIS EVOIDOS	<sup>®</sup> WB3122806-DRC-ST	REV
ODEL # ATWB 12-3L28	SCALE NTS	EVAPCO, INC.	SERIAL #	DATE 7/12/2025
NOTES:  1. (M)- FAN MOTOR LOCATION  2. HEAVIEST SECTION IS UPPER SEC  3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD GVD DENOTES BEVELED FOR WEL GVD DENOTES GROOVED FLG DENOTES PLANGE PE DENOTES PLAIN END  4. +UNIT WEIGHT DOES NOT INCLUDI ACCESSORIES (SEE ACCESSORY ID) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344] 6. *-APPROXIMATE DIMENSIONS DO NE FOR PRE-FABRICATION OF CONNE PIPING  7. 3/4" [19mm] DIA. MOUNTING HOLES RECOMMENDED STEEL SUPPORT  8. DIMENSIONS LISTED AS FOLLOWS ENGLISH FT-IN METRIC [mm]	AD AD DING  E DRAWINGS)  KPa] HOT USE CTING  REFER TO DRAWING.	FACE B PLAN VIEW	FACE C  CCESS DOOR  ACCESS DOOR  FACE A	FACE D
2'-1 1/4" [ 643]  3 5/8" [ 92]  (2) 2" [50] MPT — (4) 4" [100] BFW (4) 4" [100] BFW (5) BFW (6) 4" [100] BFW (7) BFW (	FLUID IN FLUID OUT 0 6" [ 154	8'-3 5/8" [2532]  15'-5 7/8" [4721]  * 7'-2 1/4" [2189]		1'-4 3/4" [ 425]