CLOSED CIRCUIT COOLER WB3241212-DRD-ST WB3241212-DRD-ST SERIAL # WB3241212-DRD-ST SERIAL # FACE C (a) ACCESS DOOR FFT DENOTES SEAVE IN FIREAD FFT DENOTES SEAVE IN FIREAD FFT DENOTES SEAVE IN FORM SET DENOTES SEAVE IN FIREAD FFT DENOTES SEAVE IN FORM F	DATE 12/13/2025
1. (M)- FAM MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD FPT DENOTES REMALE PIPE THREAD FPT DENOTES REVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLANGE PE DENOTES PLANGE PE DENOTES PLANGE 20 psi MIN (137 kPa), 50 psi MAX (344 kPa) 6. *APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN METRIC [mm] FACE D FACE A	
3'-11 3/4"	

HEAVIEST SECTION WEIGHT

18480 lbs+ [8385] kg+

SHIPPING WEIGHT OPERATING WEIGHT

64500 lbs+ [29260] kg+

42380 lbs+ [19225] kg+

DRAWN BY: SLR

NO. OF SHIPPING SECTIONS