| UNIT CLOSED CIRCUIT COOLER | | OOLER | EVADOO TRIC EVOIDEO | # WB3TM2408-DRC-ST | REV |
|--|---|--|---|----------------------------|--------------------|
| IODEL # | ATWB 10-4M24 | SCALE NTS | EVAPCO, INC. evapco | L # | DATE 8/26/2025 |
| 2. HÉAVI 3. MPT D FPT DI BFW C GVD D FLG DI PE DE 4. +UNIT ACCES 5. MAKE- 20 psi 6. *-APPF FOR P PIPINO 7. 3/4" [11 RECOI | AN MOTOR LOCATION EST SECTION IS UPPER S ENOTES MALE PIPE THRE ENOTES FEMALE PIPE THIS DENOTES BEVELED FOR W DENOTES GROOVED ENOTES PLAIN END WEIGHT DOES NOT INCLU ESCRIES (SEE ACCESSOR UP WATER PRESSURE MIN [137 kPa], 50 psi MAX [3] ROXIMATE DIMENSIONS DO RE-FABRICATION OF CON COMMITTED | AD READ /ELDING JDE Y DRAWINGS) 344 kPa] O NOT USE NECTING ES. REFER TO RT DRAWING. | FACE B PLAN VIEW FACE B FACE B PLAN VIEW | ACCESS DOOR | FACE D |
| (2) 2' 2'-1 1/4 [643] | 3 5/8" | FLUID IN FLUID OUT O O O O O O O O O O O O O O O O O O | 2'-6 3/8" * ['.772] * 9'-1/8" ['.2748] 15'-2 3/8" ['.4632]] 15'-2 3/8" ['.4632]] 15'-2 3/8" ['.4632]] 15'-2 3/8" ['.4632]] 11'-11'-11'3/4" ['.3651] 11'-5" ['.366] FACE A | | – 1'-5" - [432] |
| FACE B SHIPPING | | | | | |
| HIPPING WEIGHT | 29340 lbs+ [13 | 310] kg+ | OPERATING 45680 lbs+ [20725] kg+ HEAVIEST SECTION 11990 lbs+ [5440] kg+ WEIGHT | NO. OF SHIPPING SECTIONS 4 | SLR |