COCCURRENCE OF THE PROPERTY OF	JNIT	01 0050 01001117 00011	-n I			[	• D	WG. #	F REV.
TOPE PREVIOUS ENDANCE PRESENT ON SUPPRISE SCTION SUPPRISE SCTI	10DEL #		CCALE	EVAF	PCO, IN	IC. evapco	SE		F -
METRIC (nm)  (4) 4" (500) BFW FLUID IN  (4) 4" (500) BFW FLUID OUT  (5) 4" (5) 4" (6) 12" (6) 12" (7) 12" (8) 12" (7) 12"	1. (M)- FAN M 2. HEAVIEST 3. MPT DENC BFW DENC GVD DENC PE DENC PE DENC PE DENC 4. +UNIT WE ACCESSO 5. MAKE-UP 20 psi MIN 6. *-APPROX FOR PRE- PIPING 7. SERIES FI DRAIN BY 3. 3/4" [19MM RECOMME 9. DIMENSIO	SECTION IS UPPER SECTION IS UPPER SECTION IS UPPER THREAD OF THE SEVELED FOR WELD OTES BEVELED FOR WELD OTES GROOVED OTES FLANGE  TES PLAIN END IGHT DOES NOT INCLUDE RIES (SEE ACCESSORY DRAWATER PRESSURE [137 KPa], 50 psi MAX [344 KIMATE DIMENSIONS DO NOT FABRICATION OF CONNECT OTHERS.  LOW PIPING AND AUX. CROSOTHERS.  TO THE SECTION OF CONNECT OTHERS.  TO THE SECTION OF THE SEC	AWINGS) Pa] T USE FING SSOVER		·	ACCE	ESS DOOR	ACCESS DOO	FACE D
FACE B	1'- (2) 2" [50 MA	5/8"	(4) 4 Fi	14'-5 7/8" [ 154] *  6''-2 1/4" [ 1884]  1'-5" 433]	(4) 1/2" FPT VI  SERIES FLOW PIPING - (SEE NOTE 7)  AUX. CROSSOVER DRAIN - (SEE NOTE 7)	(15) (N)		2 1/2" [ <sup>1</sup> -5" [432	

HEAVIEST SECTION WEIGHT

SHIPPING WEIGHT

OPERATING WEIGHT