| INIT | CLOSED CIRCUIT C | OOLER | | | | DWG. # WB3TM2408-DRC-SF | REV. |
|--|--|---|---|-----------------------------------|-----------------------------|--------------------------------|-----------------|
| 10DEL # | ATWB 10-4L24-Z | SCALE NTS | ⊢ EVAP | PCO, INC. | evasco | SERIAL # | DATE 8/26/2025 |
| 2. HÉAVIE 3. MPT DE FPT DEI BFW DE GVD DE FLG DE PE DEN 4. +UNIT V ACCESS 5. MAKE-U 20 psi M 6. *-APPRO FOR PR PIPING 7. SERIES DRAIN E 3. 3/4" [19# RECOM 9. DIMENS | N MOTOR LOCATION ST SECTION IS UPPER SE NOTES MALE PIPE THRE, NOTES FEMALE PIPE THRE, NOTES BEVELED FOR W NOTES GROOVED OTES PLAIN END VEIGHT DOES NOT INCLUSORIES (SEE ACCESSOR') IP WATER PRESSURE IIIN [137 kPa], 50 psi MAX [3] OXIMATE DIMENSIONS DO IE-FABRICATION OF CONN FLOW PIPING AND AUX. (3) OTHERS. MM] DIA. MOUNTING HOLE MENDED STEEL SUPPOR SIONS LISTED AS FOLLOW IGLISH FT-IN | AD READ ELDING JDE Y DRAWINGS) JOHN TO THE SECTING CROSSOVER ES. REFER TO TO DRAWING. | | FACE B PLAN VIEW | ACCESS DOOR | ACCESS DOOR ACCESS DOOR CE A | FACE D |
| | ETRIC [mm] | | [7" | 1'-3 1/4" [387] | | 1 / | |
| | (4) 4" [100] BFW 4' [14' [100] IN [14' [100] | '-9" * 448] * | _ 2'-6 3/8" * [772] * [2748] (4) 4"[100] BFW | (4) 1/2" [15] FPT VENT | M) | | |
| | 2'-6 3/4" * | | FLUID OUT 15'-2 3/8" [4632] | SERIES FLOW PIPING - (SEE NOTE 7) | | | |
| (2) 2" <u>†</u> 2'-1 1/ [643 | [50] MPT — MAKE-UP 4" | | 6" * 6'-2 1/4" [1884] 1'-5" [433] | AUX. CROSSOVER DRAIN (SEE NOTE 7) | | | |
| 1 | 3 5/8" (2) 3" [80] M DRAIN 5 1/4" [133] | PT | — (2) 3" [80] MPT OVERFLOW | | | | |
| | - 41/4" [108] - 5'-11 3/4 [1822] | 1" | | 1'-5" [432] | [3031] | 2 1/2" 1'-5" [432] | |
| 9'-9 3/4" [2991] <u>FACE B</u> | | | 24'-2" | | | | |
| SHIPPING WEIGHT | 29240 lbs+ [13 | 3265] kg+ | OPERATING 45580 lbs+ | [20675] kg+ HEAVIEST SE WEIGH | CTION 11940 lbs+ [5420] kg+ | NO. OF SHIPPING SECTIONS 4 | RAWN BY: TLM |