COOLING TOWER		<u> </u>	EVADOO TNIC EVEDO		DWG. # AX142413-DRA-ST		REV.
MODEL #	AXS 14-16L24	SCALE	EVAPCO, INC.	SER	RIAL #		DATE 12/8/2025
2. HEAVIES 3. MPT DEN FPT DEN BFW DEN GVD DEN 4. +UNIT WI ACCESSO 5. MAKE-UF 20 psi MII 6. 3/4" DIA. RECOMN	MOTOR LOCATION T SECTION IS UPPER SECTIOTES MALE PIPE THREAD OTES FEMALE PIPE THREAD OTES BEVELED FOR WELI IOTES GROOVED PIES (SEE ACCESSORY DE) WATER PRESSURE N [137 kPa], 50 psi MAX [344 MOUNTING HOLES. REFER IENDED STEEL SUPPORT DE ONS LISTED AS FOLLOWS:	AD DING E DRAWINGS) kPa] TO DRAWING.	FACE B [2124]	FACE C ACCESS DOOR		(2)	FACE D LO" [250] ASME BOLT PATTERN ET
			7" _	FACE A			
[178]							
			9'-4 3/8" [2855]	(*))	OVĒ 	100] FPT ERFLOW 80] MPT KE-UP [100] FPT AIN
			6'-5 5/8" [1970]	CESS DOOR			
		-11 1/4" 8] CE B	3/8" 2'-5 3/4" 14" [350] BFV OI 15" [350	7	10'-3" [3124] 11'-1" [3378] 12'-4 1/2" [3772]		
SHIPPING WEIGHT	20000 lbs+ [9075] kç	g+	ATING 46650 lbs+ [21165] kg+ HEAVIEST SECTION 1190	00 lbs+ [5400] kg+	NO. OF SHIPPING SECTIONS	2	DRAWN BY: AWT