| COOLING TOWER   |  |                                     |                     | EVAPCO, INC. Evapeo  |                                    |                            |                          |       | #<br>AX142417-DR        | A-ST              | REV.   |
|---|--|-------------------------------------|---------------------|----------------------|------------------------------------|----------------------------|--------------------------|-------|-------------------------|-------------------|--|
| MODEL #   | (S 14-19N24  | SCALE                               |                     | EVAPCO               | J, II                              | VC.                        |                          | SERIA | _#                      |                   | DATE<br>9/3/2025                                     |
| 2. HEAVIEST S 3. MPT DENOTE FPT DENOTE BFW DENOTE GVD DENOTE 4. +UNIT WEIG ACCESSORI 5. MAKE-UP W. 20 psi MIN [1 6. 3/4" DIA. MO RECOMMEN | TOR LOCATION ECTION IS UPPER SECTION ES MALE PIPE THREAD ES FEMALE PIPE THREAD ES BEVELED FOR WELDII ES GROOVED HT DOES NOT INCLUDE ES (SEE ACCESSORY DRA ATER PRESSURE 37 kPa], 50 psi MAX [344 kF UNTING HOLES. REFER TO DED STEEL SUPPORT DRA S LISTED AS FOLLOWS: EI | ng<br>Awings)<br>Paj<br>O<br>Awing. |                     | PLAN VIEW            | 6'-11 5/8"<br>2124 ]<br>9 5/8"     |                            | FACE C<br>ACCESS DOO     | _     |                         | <b>(2)</b> 1      | <b>ACE D</b><br>LO" [250] ASME<br>BOLT PATTERN<br>ET |
|   |  |                                     | 7"<br>[ 178         |                      |                                    |                            | FACE A                   |       |                         |                   |  |
|   |  |                                     |                     | 9'-4 3/8"<br>2855 ]  |                                    |                            |                          |       |                         | ∕− 4" [10<br>OVER | 00] FPT<br>FLOW                                      |
|   |  |                                     |                     | 19'-4"<br>[ 5893 ]   |                                    |                            |                          |       |                         | — 3" [80<br>MAKE  | D] MPT<br>-UP  |
|   |  |                                     | [                   | 9'-11 5/8"<br>3038 ] | <b>A</b>                           |                            | ACCESS DOOR              |       |                         | ∕-4" [1(<br>DRAI  | 00] FPT<br>N   |
|   |  |                                     |                     |                      | , <del>† <u>†</u></del>            | 1                          |                          |       | 10' 2"                  |                   |  |
|   | 13'-<br>[ 424<br>FACI  | -11 1/4"<br>8 ]<br><b>E B</b>       |                     | 3/8"<br>[ 10 ]       | "<br>1/2"<br>1 ]<br>3 7/8"<br>98 ] | 14" [350                   | OUTLET  24'-9"  [ 7544 ] |       | 10'-3"                  |                   |  |
| SHIPPING<br>WEIGHT  | 21470 lbs+ [9740] kg   | +                                   | OPERATING<br>WEIGHT | 48120 lbs+ [21830] k | g+                                 | HEAVIEST SECTION<br>WEIGHT | 12110 lbs+ [5495] kg-    | + N   | O. OF SHIPPING SECTIONS | 2                 | DRAWN BY: AWT  |