UNIT CONDENSER			EVAD		IC ev	gpeo °	DWG. # WV050906-DRC-ST	REV.
MODEL #	LRC-108	CALE NTS	EVAP	CO, II	VC.	1	SERIAL #	DATE 5/3/2024
FPT DENOTES BFW DENOTE GVD DENOTE FLG DENOTES PE DENOTES 3. +UNIT WEIGH ACCESSORIE 4. 3/4" [19mm] DI RECOMMEND 5. DIMENSIONS	S MALE PIPE THREAD S FEMALE PIPE THREAD S BEVELED FOR WELDII S GROOVED S FLANGE PLAIN END T DOES NOT INCLUDE S (SEE ACCESSORY DRA A. MOUNTING HOLES. R ED STEEL SUPPORT DR. LISTED AS FOLLOWS: EI	NG AWINGS) EFER TO AWING NGLISH FT IN METRIC] [mm]	FACE B 5'-5'	5/8",		FACE C		FACE D
USE FOR PRE 7. MAKE-UP WA	ATE DIMENSIONS DO NO -FABRICATION OF CONN FER PRESSURE a] MIN, 50 psi [344 kPa] Ma	NECTING PIPI						(*)
					b	15'-2 1/4" [4629] FACE A		_
-	2'-6 3/8" * -						[6'-3" [1905]	_
4" [100] PE - REFRIG IN			1 1					
4" [100] PE – REFRIG OUT		1'-7 [4	3'-7 1/2" 1/2" * [1106] 95] * 6'-7 3/4" [2026]			4/1		6'-7 3/4" [2026]
3 1/4" TYP. →		F	5 1/4" *			CCESS		<u> </u>
		(M)						1'-8 1/8" [511]
3" [80] MPT — OVERFLOW		- 4	2 5/8"	-		8'-5 3/8" [2575]	─1" [25] MPT MAKE-UP	ACCESS DOOR
2" [50] MPT — DRAIN	5'-5/8" [1540]	'-8 7/8" [530]	1'-	1 5/8" 346]		15'-2 1/4" [4629] FACE A		
	FACE B					<u>-</u>		
SHIPPING WEIGHT	5250 lbs+ [2385] kg-		DPERATING 8070 lbs+ [3	665] kg+	HEAVIEST SECTION WEIGHT	5250 lbs+ [2385] kg+	NO. OF SHIPPING SECTIONS 1	DRAWN BY: TLS