NOTES 1. (M) F AN MOTOR LOCATION 1. (M) F AN MOTOR LOCATION 3. MPT DENOTES MALE PIPE THERAD BEYN DENOTES MALE PIPE THERAD BEYN DENOTES RALE PIPE THERAD BEYN DENOTES RALE PIPE THERAD BEYN DENOTES RALE PIPE THERAD BEYN DENOTES REVIEW THE PIPE THERAD BEYN DENOTES REVIEW THE PIPE THERAD BEYN DENOTES REVIEW THE PIPE THERAD COULCOMME TO DOES NOT NOLLOGE A CHARGE TO RECOMMENDED STEEL SUPPORT DAYS BY A DAYS (344 APa) 1. (2) # (100) BEYN 1.	CLOSED CIRCUIT COOLER	FVADCO	TNC Evap		wg. # WX409184810P-DRA-ST	
1. (M) FAN MOTOR LOCATION 2 1. (M) FAN MOTOR LOCATION 2 1. (M) FAN MOTOR LOCATION 3 1. (M) FACE B 1. (M) MOTOR LOCATION 3 1. (M) FACE B 1. (M) MOTOR LOCATION 3 1. (M) FACE B 1. (M) MOTOR LOCATION 3 1. (M) FACE B 1. (M) MOTOR LOCATION 3 1.	MODEL# ESW4 9-45G18-LP SCALE NTS	LVAPCO		S	SERIAL #	DATE: 8/26/2025
8. "-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 9. COIL CONNECTIONS LOCATED ON FACES B AND D PACE B & D COIL CONNECTIONS 2.8" 2.9" 2.2 3/8" [670] 2.2" 2.10 3/4" 2.828] FACE B & D COIL CONNECTIONS 2.3" [688] 33/8" [88] 41/4" 107-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090] 10-1 5/8" [3090]	BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. 3/4" [19MM] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING 6. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 7. DIMENSIONS LISTED AS FOLLOWS:	(2) 4" [100] BFW	PLAN VIEW (2) 4" [100] BFW FLUID OUT	(M)	(M)	FACE D
22-8" (2-2-3/8" (670) *2-10-3/4" (883) **FACE B & D **COIL CONNECTIONS **COIL CONN	[METRIC] [mm] 8. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPIN	NG O	* 2'-10 1/2" [876]	FACE	<u> </u>	
2' [S0] MPT	9. COIL CONNECTIONS LOCATED ON FACES BAN	10 D	* 2'-2 3/8" [670]			-1'-0 7/8" [327]
2" [50] MPT VENT VENT VENT VENT VENT VENT VENT VEN		[813] FACE B & D	[883]	[M] ACCESS DOOR	L J	9'-3 1/4" [2826]
3 3/8" [86] 4 1/4" [107] 5 1/4" [132] 8'-5 1/2" 1'-6 3/8" [465] 2'-2 1/4" [667] 18'-0" [5486] FACE A	MAKE-UP 2" [50] MPT —	3" [80] MPT OVERFLOW	(2)1/2" [15] FPT VENT			
3 3/8" [86] — 4 1/4" — 2'-5 5/8" — 2'-2 1/4" — 18'-0" — [5486] — [132] — 8'-5 1/2" — FACE A				0 0 0		
	4 1/4" [107] 5 1/4"	2'-5 5/8"	2'-2 1/4" [667]	[5486	6]	
FACE B						
	SHIPPING 22230 lbs+ [10085] ka+ OPER	ating 31470 lbs+ [14275] ka+	HEAVIEST SECTION 15430	lbs+ [7000] kg+	NO. OF SHIPPING SECTIONS 2	DRAWN BY: AWT