EVAPCO, INC. PMRC 955 OPAL NTS WHE PANAFORD LOADING. 2 MPT 1000TES MALE PER 1 PRED WHE PANAFORD LOADING. 2 MPT 1000TES MALE PER 1 PRED WHE PANAFORD LOADING. 2 MPT 1000TES MALE PER 1 PRED WHE PANAFORD LOADING. 2 MPT 1000TES MALE PER 1 PRED WHE PANAFORD LOADING. 3 AND A PRED ***FORD TOTAL PANAFORD CHANNES, A PRED ***	UNIT CONDENSER		EVADCO 1		/dpco	wg. # CEWR122410-DRA-ST	REV -
### NATIONAL COCKING ### NATIO	MODEL # PMRC-956 SCALE N	ΓS	EVAPCO, I		SI	ERIAL#	
[937] [1743] OVERSIZED ACCESS DOORS 3180 MPT 3780 MPT 3780 MPT OVERSIZED OVERSIZED 3780 MPT OVERSIZED 11-7 1/8" [486] 11-7 1/8" [486] FACE B FACE A FACE B FACE A	1. (M)- FAN MOTOR LOCATION. 2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS). 4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [344 kPa] MAX. 6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] [mm] 7. * - APPROXIMATE DIMENSIONS DO NOT			B\$\$\$\$			FACE D
SRIPPING 39760 lbs+ [18035] kg+ UPERATING 49800 lbs+ [22590] kg+ HEAVIEST SECTION 14530 lbs+ [6595] kg+ 39760 lbs+ [3000] kg+ WEIGHT 14530 lbs+ [6595] kg+	OVERSIZED ACCESS DOORS 3"[80] MPT MAKE UP 3"[80] MPT DRAIN 2'-5"[737] 1'-8" [508] 3 7/8" [98] 5'-0 3/8" [1534] SHIPPING 20760 lbs. [19035] kg.	(2) 3"[80] MPT OVERFLOW 0 3/8" 16] OPERATING	9'-11" [3023] * 8'-6 3/8" [2600] HEAVIEST SECTION	[7337	<u>E A</u>	1'-6" [457]