| CONDENSE PARC-1203 BEALF NTS PARC-1203 BEALF NTS NOTE: 1. (10.5 FARMED ALL ONE NEEDED) FOR REPORTED AND SHARE OF THE READ O | UNIT CONDENSER | | EVADCO TNC evapco | | /apco | OWG. # CEWR122410-DRA-ST | REV | - |
|--|---|---|---|------------------------|----------------------|--------------------------|-----------|----------|
| ACCESSIONS ON FOUNDRISE ON THE PRINCE OF THE | PMRC-1203 SCALE N | S | EVAPCO, I | INC. | S | ERIAL# | DATE: | 8/9/2025 |
| OVERSIZED ACCESS DOORS 3"[80] MPT DRAIN 9'-11" [3023] * 8'-6 3/8" [2600] | 1. (M)- FAN MOTOR LOCATION. 2. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END 3. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS). 4. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 5. MAKE-UP WATER PRESSURE 20 psi [137 kPa] MIN, 50 psi [344 kPa] MAX. 6. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN [METRIC] [mm] 7. * - APPROXIMATE DIMENSIONS DO NOT | | | | | | | FACE D |
| 1'-8" [508] | OVERSIZED ACCESS DOORS 5 1/8" [130] 3"[80] MPT MAKE UP 3"[80] MPT DRAIN 2'-5"[737] 1'-8" [508] 3 7/8" [98] 5'-0 3/8" [1534] SHIPPING 40690 lbg. [49455] kg. | 3] O REFRIG IN O REFRIG OUT (2) 3"[80] MPT OVERFLOW 3/8" 6] E B | 15'-0 1/2" [4585] 9'-11" [3023] * 8'-6 3/8" [2 1'-7 1/8" [486 | 2600] HEAVIEST SECTION | [733] <u>FACE</u> | 7/8" | DRAWN BY: | |